

HVB10

High-voltage bridge

技术咨询和询价：010-68940148



- Top measurement and accuracy
- Automatic test sequence
- Bi-polar prelocation for the elimination of external influences
- Detection and indication of wrong connections
- Only one HV connection cable
- Completely independent of the parameters of auxiliary lines
- Megger's easyGo principle

康高特-MEGGER HVB10高压电桥电缆故障定位仪DESCRIPTION

Megger's HVB10 is a highly accurate high-voltage bridge designed to locate cable and sheath faults, perform sheath testing, and pinpoint sheath faults, especially suited also for long HV cables.

With its top resolution, intermittent fault detection function, and load adaptation for faster cable charging, the HVB10 is an indispensable tool for all utilities that want to reduce downtime and facilitate repair of power and for example pilot and communication cables.

The HVB10 has two different methods for fault location:

- the **standard mode**, which provides good results for typical sheath faults with fault resistances of up to some hundreds of kilo Ohms and shield cross sections in the range of 25 to 50 mm². This measurement is typically done in approx 30 seconds
- the high **accuracy mode**, which takes approximately 1 minute for the algorithm to complete, but will utilize the full potential of the measuring and control circuits of the instrument. Thus, it is ideally suited for prelocating difficult, high-resistive faults (e.g. in the inner insulation of PILC cables). An intermittent fault detection algorithm is applied to gain a result under even worse conditions with sparking faults.

康高特-MEGGER HVB10高压电桥电缆故障定位仪 Why HVB10?

Why do you need an HV bridge when you have ARM based prelocation?

Because it locates faults where the otherwise perfect reflection based technologies have limits, for example on long cables as subsea cables.

- TDR reflection based technologies have very large reflections on crossbonded cables, which prevent longer ranges
- Reflection measurements are based on an impedance measurement, while the HVB10 measures resistance. Resistance- and impedance values can be completely different while having the same cause.

The HVB10 prelocation measurement and the common prelocation by reflection measurement or ARM Arc Reflection Measurement provide complementary information, which is very helpful in case of difficult faults, where critical decisions have to be done on a reliable base.

Cable fault location

The HVB10 accurately prelocates cable interruptions and short-circuit faults, and detects high-resistance conductor faults that cannot be prelocated with impulse reflection based methods.

The HV bridge is equipped with a strong discharge unit which allows the safe discharge of cables with a capacity of up to 25 µF. Prior to each test, a capacity measurement ensures that the expected discharge energy does not exceed these parameters and damage the HVB10. This makes it very suitable for very long cables and their parameters.

Sheath fault prelocation

The prelocation of sheath faults takes place automatically. The only parameters that need to be entered are the peak test voltage and the cable length. If the cable length is not available, the fault distance is displayed as a percentage of the length.

The HVB10 evaluates all measurements automatically, providing the user with a report of the test results and a statement about the sheath condition.

Sheath fault pinpointing

The HVB10 provides two possibilities for sheath fault pinpointing:

- By means of the standard pulsed DC and the step voltage method (in combination with an earth fault probe such as our ESG NT2)
- by means of 3 or 4.8 Hz signal and A-frame

The power can be supplied either from the mains, via the wide range AC input from 88 V to 264 V, or by using the integrated rechargeable battery for minimum of 2 hours operation. This battery can also be charged by a 12/24 DC input.

TECHNICAL DATA*

Output voltage	0 ... 10 kV DC, bi-polar
Output current	200 mA @ 0.5 ... 1.5 kV, 60 mA @ 5 kV, 30 mA @ 10 kV
Max. test object capacity	25 µF
Test voltage	0 ... - 10 kV
Prelocation	
Method	Voltage drop method (automatic.)
Accuracy	± 0,1 %
Pinpointing	0 ... - 10 kV DC, pulsed
Voltage	0.5:1 / 1:2 / 1.5:0.5 / 1.5:3.5
Pulse rate	3 and 4.8 Hz for A-frame
Supply voltage	88 V ... 264 V, 50/60 Hz
DC Supply (charge only)	12/24 V DC
Battery	Int. NiMH battery (340 Wh)
Battery operating time	approx. 2 hours
Power consumption	max. 500 VA
Display	320 x 240 pixel LCD, LED rear light
Interfaces	USB port
Storage	2 GB Flash memory for System and data
Data logging	by USB stick
Operating temperature	- 25° C ... + 55° C max. 93 % rel. humidity
Storage temperature	- 40° C ... + 70° C
Dimensions (W x H x D)	500 x 457 x 305 mm
Weight	25 kg
Protection class acc. IEC 61140	I (Protective earthing)
Protection class acc. IEC 60529	IP 53 (with closed lid)

Options

Connection set for HV armatures



HVB10 High-voltage bridge

Max. fault resistance @ 10 kV with a 1 km cable with defined cross section. Fault position @ 50% of cable length	Ø mm ²	25	150	240	300	630	1200
	CU conductor	670 MΩ	110 MΩ	69 MΩ	55 MΩ	26 MΩ	13 MΩ
	AL conductor	1 GΩ	176 MΩ	110 MΩ	88 MΩ	42 MΩ	22 MΩ

Max. fault resistance @ 10 kV with a 1 km cable with defined cross section. Fault position between 10% and 90% of cable length	Ø mm ²	25	150	240	300	630	1200
	CU conductor	132 MΩ	22 MΩ	13 MΩ	11 MΩ	5,2 MΩ	2,7 MΩ
	AL conductor	209 MΩ	34 MΩ	21 MΩ	17 MΩ	8,3 MΩ	4,3 MΩ

ORDERING INFORMATION

Product	Order No.
HV Measuring Bridge System HVB10-1	1012574
Consisting of:	
HVB10-1	1004820
USB-Drive with Software EasyProt	890017185
Set of cables for HVB10 in accessory bag	1004032
Consisting of:	
HSK 40-6 HV Test lead, HVB10-1 6 m	1 piece 2008422001
EK 11 Earth lead 5 m (green/yellow)	1 piece 820024352
AK 49-B Clip (green/yellow)	1 piece 810003846
MK 053-B Test lead (Blue)	2 pieces 810003176
AK 43-B Clip (blau)	4 pieces 810003848
LK 13 Vehicle charging adapter 3,5 m	1 piece 810000006
NKG 1 Power cord 2,5 m, 3x1 mm ² grey	1 piece 810000024
Power cord 2,5 m, 3x1 mm ² grey (UK-Version)	1 piece 118307335
Power cord (US-Version) JEC 2 m	1 piece 502025220
HVB10, Manual de	83230
HVB10, Manual en	83041
Options:	
Connection set for HV Armatures	1003344
Consisting of:	
HKZ HVB-1 Connection Clamp (Black)	4 pieces 1003332
HKZ HVB-2 Connection Clamp (Red)	2 pieces 1003333
Cable binder, velcro, (black)	8 pieces 820020537
Manual for connection Set HVB10	2003767

The information in this document is subject to change without notice and should not be construed as a commitment by Megger Germany. Megger Germany assumes no responsibility for any errors that may appear in this document.